

## INDUSTRIAL SPEAKER AMPLIFIERS

### FEATURES AND BENIFITS

**Model 750-401** Indoor amplifier  
 Consist of: - model 751-001 Amplifier  
 - model 702A Enclosure



**Model 670-001** Hazardous area  
 indoor amplifier



- Rugged construction and premium-grade components provide reliable operation in harsh environments.
- Powerful 12Watt amplifier allows effective communication in areas of extreme noise.
- Ample space in enclosure and double row terminal block for easy installation.
- Factory Mutual & CSA approved for hazardous locations.
- Modular design reduces spare part investment.

**Model 760-001** Outdoor amplifier  
 (Aluminium. Valox housing not shown)

Above amplifiers provides quality paging coverage for many applications. Rugged enclosures and high-quality amplifier components provide dependable operation in even the harshest location.

Speaker amplifiers are used with Page/Party (See Pub 0003-002) and Electro-Sound II (see Pub 0003-016) paging systems.

The indoor stations are housed in dust-tight, 2 mm cold-rolled steel enclosures finished with textured polyurethane paint.

The outdoor stations are housed into a non corrosive VALOX housing or an aluminium housing.

### Specifications.

Power	: 120VAC 50/60Hz 50VA consumed (4VA idle).	
Audio amplifier	: 12Watt RMS. Frequency range 250-4KHz	
Microphone	: Dynamic 10 Ohm noise cancelling.	
Controls	: Speaker volume.	
Temperature range	: Minus 30C° to +70C°	
Shipping weight	: Indoor Amplifier :5 Kg	Outdoor Aluminium: 7Kg
		Valox : 6,5Kg
Protection	: IP42 (Indoor)	IP65 (Outdoor)