

STANDARD SIMPLEX TALK BACK INTERCOM



Model PC2002DX



Model PC2010AX
(Connection box not shown)



Model PC 20005AX/GOS
(Connection box not shown)



Model PC 2010/FL/GOS
(Connection box not shown)



Model PC 2015/GOS
(Connection box not shown)

FEATURES AND BENIFITS

- Selective calling and “All Call” function.
- Visual and acoustical indication on masterstation of caller.
- Available in 1 up to 500 substations.
- Easy to use and to install. No software required.
- Separate volume button for speak and listen.
- Only one (1) pair per substation. Star wiring with standard telephone cable up to 1Km away.
- Suitable for desk or wall mounting.
- Optionally gooseneck microphone (reducing ambient noise) and flush mounted version.

OPTIONS

Add abbreviations behind the model number in order to obtain the requested option(s).

- FL** = Flush mount version for installation into a console.
GOS = Gooseneck microphone avoids pick up of ambient noise.

The above intercom units providing simplex communication (push to speak, release to listen) for industrial applications such as fuel loading/unloading skids for trucks and gate entry applications. The units can be used as well to drive explosion proof substations (use model PR-96018/EX) in areas where selective calling is required.

The same units exist as well in semi-duplex. (Speak/listen function managed by your voice). See datasheet Pub-0003-014 for corresponding slave talk back stations.

Specifications

Wiring : One (1) pair to every substation in star wiring. Max length 1Km with 0,6mm2
 Temperature range : 0C° to +50C°
 Protection : IP40
 Construction : ABS

	PC2002	PC2005	PC2010	PC2015	PC2020
Power requirements	: 12VDC/4VA 230VAC adapter incl.	: 12VDC/10VA 230VAC via conn. Box.	: 230VAC/20VA 230VAC via conn. Box.	: 230VAC/30VA 230VAC via conn. Box.	: 230VAC/40VA 230VAC via conn. Box.
Sound power	: 1Watt	: 4Watt	: 4Watt	: 4Watt	: 4Watt
Capacity substations	: 2	: 5	: 10	: 15	: 20
Dim. desktop (LxWxD)	: 240x120x62	: 240x187x62	: 240x187x62	: 240x297x62	: 240x297x62
Dim. Conn. Box (LxWxH)	: N.A.	: 205x140x65	: 205x140x65	: 205x140x65	: 205x140x65
Shipping weight	: 1Kg	: 2Kg	: 3Kg	: 3Kg	: 3kg

PRONOR N.V.
 Liefkensstraat 35A
B-9032 GENT

TEL: (+) 32-9-257 08 80

www.pronorbelgium.com
 E-mail: info@pronor.be