

IP BASED MASTER STATION MODEL CD800-K32 up to K96.



MODEL CD800-K32/GOS/DIS/HS

Master station with 32 selection buttons, gooseneck microphone, touch screen panel and handset
(Models CD800-K64 and K96 will have additional push button panels)

Features

- Modular Control Desk solution.
- Up to 3 push buttons panels of each 32 direct dial buttons. (Total of 96 buttons)
- IP50 rating.
- Connection for headset, handset or gooseneck microphone available.
- Touch screen panel providing seamless integration of third-party software products.

Options



K32
keyboard 32 buttons



GOS
Gooseneck microphone



HS
Handset for privacy



DIS
Touch screen panel

Specifications.

Construction : Poly-carbonate.
 Mounting : desk top.
 Power requirements: 20-30VDC/10VA.
 Cabling : CAT-5 cable. Maximum 90 meter and separate power supply.
 Microphone : Electret. External connection for headphone- headset or handset.
 Audio amplifier : Class "D" at 2,5Watt. Built in 2 speakers of 8 Ohm.
 Inputs/Outputs : 3 input contacts, 2 relay output contacts 30V/1A
 Adjustments : volume and ringing tone. Use the up/down arrow.
 Frequency range : 200Hz - 16KHz
 Display : Small display built in main unit:
 - 3,5" TFT display monochrome (CD800P) or colour (CD810P). Resolution 320x240 pixels
 Large display touch screen panel:
 - 8,4" TFT display colour. Resolution 800x600 pixels. Fan-less industrial PC concept.
 Keyboard : Up to 96 illuminated LED membrane selection switches. 3 colour LED function.
 Technology : latest DSP speech technology for clear communication.
 Protection : IP50
 Temperature range : 0C° to +70C°. (95% humidity)
 Dimensions (WxHxD): Each panel is 262x196x45mm (Gooseneck not included)
 Shipping weight : 1,1Kg per panel.