

EXPLOSION PROOF OUTDOOR ANALOGUE TELEPHONE



Model AUTELDAC 5

(Available with steel or PVC coil cord. Picture shows model 212-02-5028-400 with PVC coil cord)

FEATURES AND BENIFITS

- Integrated ringer and built in relay contact for external beacon or bell.
- DTMF keypad. Suitable for wall or desk mounting.
- ATEX approval for use in Zone 1, Zone 2, Zone 21 and Zone 22.
- Robust and weather resistant. Carbon loaded glass –filled polyester housing.
- Headset option. No moving parts.

Options



Part 100-02-0598-001
(Headset)



PSTN
(Free standing mounting pole.)



PTK
(Pole topkit.)





SMK
(Side mounting kit)

Model AUTELDAC 5 is an analogue outdoor explosion proof telephone built to withstand operator abuse and environmental extremes. The telephone is certified for safe operation in hazardous areas for Zone 1 Group IIC and T5.

This telephone exist as well without keypad in order to operate as emergency or hotline telephone. Just lifting the handset will automatically ring a pre-programmed phone number.

Specifications.

Construction	: carbon loaded glass filled polyester. Black colour.
Power requirements	: 45...60V drawn from the analogue telephone line.
Ringing tone	: 90dbA at one (1) meter.
Internal relay contact	: Dry N.O. contact max 250VAC/3A Max.300Watt.
Hook switch	: Reed contact.
Dialling system	: Pulse and DTMF (switchable)
Temperature range	: Minus 20°C to +60°C
Protection	: IP66
Approvals	: ATEX EEXe m ib IIC T5  II 2 GD &  II 2 G ATEX Gas & dust
Dimensions (LxWxD)	: 292x190x134mm
Shipping weight	: 3,1Kg