


## INDOOR OFFICE LOUDSPEAKERS



**Model B-406-8 (T)**

### Specifications.

Construction : ABS housing.  
 Mounting : Two captive screws. wall mounting  
 Power rating : 6Watt RMS  
 SPL (1Watt/1mtr) : 90dB. (97 at full power)  
 Impedance : 8 Ohm or 70V/100V. (6 power taps)  
 Dispersion 1KHz : 170 degree  
 Frequency range : 180Hz - 14000Hz  
 Colour : White  
 Dimensions (LxWxD): 210x210x66mm  
 Shipping weight : 1,1Kg  
**Option** : POT = Built in volume button.



**Model EDL-26**

### Specifications.

Construction : ABS housing self-extinguishing acc. UL-94V0 with metal front grille.  
 Mounting : Rotating lock nut system accepts ceiling thickness between 10 to 40mm.  
 Power rating : 10Watt RMS  
 SPL (1Watt/1mtr) : 86dB. (95dB at full power)  
 Impedance : 100V (4 power taps)  
 Dispersion 1KHz : 160 degree  
 Frequency range : 80Hz – 14KHz  
 Colour : White  
 Dimensions (ØxD) : 230x75mm. Cut-out in ceiling Ø200mm  
 Shipping weight : 0,91Kg  
**Option** : POT = Remote installed volume button.



**CP6-8(T)**



**Model CP66-8 (T)**

### Specifications.

Construction : ABS housing.  
 Mounting : Three captive screws wall mounted.  
 Power rating : 6Watt RMS  
 SPL (1Watt/1mtr) : 86dB. (94 at full power)  
 Impedance : 8 Ohm or 70V/100V. (6 power taps)  
 Dispersion 1KHz : 180 degree  
 Frequency range : 170Hz - 18000Hz  
 Colour : White RAL 9010  
 Dimensions (LxWxD): CP-6 : 195x150x70mm  
 CP66 : 270x150x70mm

Shipping weight : 0,75Kg

### Option:

POT = Built in volume button.  
 (Model CP6-8(T) only.)



Above models are indoor loudspeakers suitable for Public address systems, alarm evacuation systems and background music distribution.

The B-406-8(T) is typically used for technical rooms like substations, auxiliary rooms. The EDL-26 is a false ceiling speaker for offices, corridors, canteens and locker rooms applications.

The models CP-6T and CP66T are stylish designed speakers for offices, corridors and reception halls.