

ANALOGUE PROFESSIONAL INTERCOM STATIONS



Model EE400G

<u>Specifications.</u>	
Construction	: Grey or black moulded shock proof ABS provided with 3mtr connection cable with RJ 11 connector.
Mounting	: Desk top or wall mounted with bracket EW401G.
Power requirements	: Drawn from the central exchange.
Cabling	: Standard telephone cable 2x2x0,6mm2 (2Km)
Microphone	: Electret
SPL (1Watt/1Mtr)	: 82dB at 50-Ohm speaker.
Frequency range	: 200Hz - 12KHz
Protection	: IP50
Keyboard	: Encapsulated REED contacts.
Temperature range	: Minus 40C to +90C. (95% humidity)
Dimensions (LxWxD)	: 230x66x54mm
Shipping weight	: 0,4Kg



Model EE401G

Construction	: Grey or black moulded shock proof ABS provided with 3mtr connection cable with RJ 11 connector.
Mounting	: Desk top or wall mounted with bracket EW401G.
Power requirements	: Drawn from the central exchange.
Cabling	: Standard telephone cable 2x2x0,6mm2 (1,8Km)
Microphone	: Electret
SPL (1Watt/1Mtr)	: 82dB at 50-Ohm speaker.
Frequency range	: 200Hz - 12KHz
Protection	: IP50
Keyboard	: Encapsulated REED contacts.
Display	: 6x16 segments LCD
Temperature range	: Minus 40C to +90C. (95% humidity)
Dimensions (LxWxD)	: 230x66x54mm
Shipping weight	: 0,4Kg



Model EE472B

(Model EE470 will have no display)

Construction	: Grey (G) or black (B) moulded shock proof ABS including 3mtr connection cable with RJ 11 connector.
Mounting	: Desk top.
Power requirements	: Drawn from the central exchange.
Cabling	: Standard telephone cable 2x2x0,6mm2 (1,8Km)
Microphone	: Noise compensating gooseneck microphone.
SPL (1Watt/1Mtr)	: 82dB at 50-Ohm speaker.
Frequency range	: 200Hz - 9000Hz
Protection	: IP50
Keyboard	: Encapsulated REED contacts.
Display	: 6x16 segments LCD
Temperature range	: Minus 40C to +90C. (95% humidity)
Dimensions (LxWxD)	: 230x66x54mm
Shipping weight	: 0,4K



Model EE472G/FL

(Model EE470G/FL will have no display)

Construction	: Grey or black moulded shock proof ABS with aluminium mounting plate.
Mounting	: Flush mounted.
Power requirements	: Drawn from the central exchange.
Cabling	: Standard telephone cable 2x2x0,6mm2 (1,8Km)
Microphone	: Noise compensating gooseneck microphone.
SPL (1Watt/1Mtr)	: 82dB at 50-Ohm speaker.
Frequency range	: 200Hz - 9000Hz
Keyboard	: Encapsulated REED contacts.
Display	: 6x16 segments LCD
Temperature range	: Minus 40C to +90C. (95% humidity)
Dimensions (HxWxD)	: 260x132x50mm
Shipping weight	: 1Kg

Above models are indoor intercom masterstations for office, stock rooms, and administration applications.

The communication is semi-duplex (speak/listen function controlled by voice). All stations are provided with a red optical indication soon the microphone of the station is activated.