

INDUSTRIAL ANALOG TELEPHONES



Model 246-001
Indoor telephone



Model 256-001
Weatherproof telephone

FEATURES AND BENIFITS

- Extreme operating temperature. Suitable for wall mounting.
- Anti-Corrosive enclosure.
- Robust and IP65 weather resistant.
- Noise cancelling microphone.
- Electronic ringer. No moving parts.
- Tropicalised (Conformal coated) electronic printed circuit board avoiding humidity problems on electronic parts.

Options

Add below abbreviations next to the part number in order to obtain the options.

SK = Spring kit for door. (Model 256-001 only)

AC = armoured coil cord.

TWIN_(FSK) = External flash/sounder. See datasheet Pub-0003-029 for details.

LD = Door lock. (Model 256-001 only)



TWIN_(FSK)

Models 246-001 and 256-001 are industrial indoor (246-001) or outdoor (256-001) telephones built to withstand operator abuse and environmental extremes. The telephone has no moving parts which provides the user with a high level of reliability. Both types will have standard receiver volume knob built into the handset and are provided with a noise-cancelling microphone.

This telephone exists as well without keypad in order to operate as emergency or hotline telephone. Just lifting the handset will automatically ring a pre-programmed phone number.

Specifications.

Power requirements	: 24VDC...60VDC non polarity sensitive and drawn from the telephone line. Current: 20mA (max 60mA)
Ringing tone	: 91dB(a) at 0,5 meter. (84dB(a) with door closed)
Ringer equivalent	: REN 1.3B
Hook switch	: Reed contact.
Dialling system	: DTMF
Temperature range	: Minus 40C° to +60C°
Protection	: IP32 (model 246-001) IP65 (model 256-001)
Dimensions (HxWxD)	: Model 246-001 : 242x204x175mm : Model 256-001 : 335x239x188mm
Shipping weight	: Model 246-001 : 2,6Kg Model 256-001 : 3,7Kg