

MODEL GEC-480 COUNTER INTERCOM SYSTEM.



Model GEC 480

Specifications GEC-480.

Construction : black moulded shock proof ABS.
 Mounting : Free standing on desk. Possibilities for flush mounting.
 Power requirements: 230VAC/5VA by means of included adapter.
 Microphone : Electret noise compensated gooseneck.
 Speech distance : Gooseneck side = 0,5 meter
 Customer side = 1 meter.
 SPL (1Watt/1Mtr) : 82dB at 50-Ohm speaker. 95 dB at full power.
 Frequency range : 200Hz - 12KHz
 Protection : IP44
 Keyboard : Encapsulated REED contacts.
 Temperature range : 0C° to +50C°. (80% humidity)
 Dimensions (HxLxW): 179x230x57 Gooseneck 430mm
 Shipping weight : 1,2Kg

Specifications Q400.

Model Q400 is the indoor microphone to be installed at the client side and included when ordering model GEC-480
 Construction : black moulded shock proof ABS.
 Mounting : To be fixed with glue against the window
 Cable length : 3 meter
 Temperature range : Minus 25C° to +70C°.
 Dimensions (LxWxH): 43x21x13mm

Choice of speaker at client side.

The unit requires a speaker, which is included into the shipment, to be installed at the client side. See below available choice of speakers. Please mention your choice when ordering.



CP6-8
(Stylish design)



B406-8
(Wall mount)



EDL-26-8
(False ceiling mount)

Option

The standard indoor microphone model Q400 may be replaced by an optionally weatherproof "In-glass" microphone model MIC-480.



Model MIC-480
(Weatherproof in-glass microphone)

The model GEC 480 has been designed for high level of quality of through-glass communication.

The unit has a built in speech processor for high volume open duplex (talk and listen at the same time) and a feed back protection. This makes the unit suitable for a widely varying acoustic environment and is the ideal counter intercom for cashiers, porters, security personnel etc..

A clean solution for sterile environments, security interlocks or simply as a one-to-one between acoustically separated rooms.

The unit includes a standard glass fixed microphone (model Q400) or can be supplied with an optional in-glass weatherproof microphone model MIC-480.

MODEL GEC-882 COUNTER INTERCOM SYSTEM WITH BUILT IN 15WATT PAGING AMPLIFIER.



Model GEC 882

Specifications GEC-882.

Construction : Black moulded shock proof ABS.
 Mounting : Free standing on desk. Possibilities for flush mounting.
 Power requirements: 230VAC/20VA by means of included adapter or 12 to 18VDC at 1,2A.
 Microphone : Electret noise compensated gooseneck.
 Speech distance : Gooseneck side = 0,5 meter
 Customer side = 1 meter.
 Amplifier audiopower: - Inside amplifier 0,6Watt equal to 82dB at 1 mtr
 - Outside amplifier 10/15Watt at 4-16 Ohm.
 Frequency range : 500Hz - 15KHz
 Protection : IP30
 Keyboard : Encapsulated REED contacts. Total 15 keys
 Temperature range : 0C° to +50C°. (Max. 80% humidity)
 Dimensions (HxLxW): 179x280x230 Gooseneck 422mm
 Shipping weight : 1,2Kg

Specifications Q400.

Model Q400 is the indoor microphone to be installed at the client side and is included when ordering model GEC-882
 Construction : black moulded shock proof ABS.
 Mounting : To be fixed with glue against the window
 Cable length : 2,8 meter
 Temperature range : Minus 25C° to +70C°.
 Dimensions (LxWxH): 42x24x13mm

Choice of speaker at client side.

The unit requires a speaker, which is included into the shipment, to be installed at the client side. See below available choice of speakers. Please mention your choice when ordering.



CP6-8
(Stylish design)



B406-8
(Wall mount)



EDL-26-8
(False ceiling mount)

Option

The standard indoor microphone model Q400 may be replaced by an optionally weatherproof "In-glass" microphone model MIC-480.



Model MIC-480
(Weatherproof in-glass microphone)

The model GEC 882 is a digital desktop counter intercom designed for high level of quality of through-glass communication.

The unit has a built in speech processor for high volume open duplex (talk and listen at the same time) and a feed back protection. This makes the unit suitable for a widely varying acoustic environment and is the ideal counter intercom for cashiers, porters, security personnel etc..

The modular construction of the system allows any number of desktop counter intercom systems to be combined into one system.

The built in 10-15Watt power audio amplifier allows you to use the unit as well as Public Address system.

The unit includes a standard glass fixed microphone (model Q400) or can be supplied with an optional in-glass weatherproof microphone model MIC-480.