

## HEAVY DUTY DIGITAL HANDSFREE INTERCOM STATIONS.



**Model EE8158M**

Digital heavy duty handsfree station 6 call buttons

Specifications.

Construction : Orange moulded RAL 2004 polyester fiber reinforced.  
 Mounting : wall mounted with 2 screws size M5.  
 Power requirements: 24VAC at 40VA.  
 Cabling : Standard telephone cable 1x2x0,8mm (2Km)  
 Microphone : Noise cancelling  
 Audio amplifier : Class "D" at 25Watt at 8 Ohm external speaker.  
 Built in speaker sound pressure: 96dB/1W/1mtr.  
 Frequency range : 200Hz - 7KHz  
 Inputs : 2 inputs.  
 Outputs : 2 outputs 30Vmax/3A.  
 Protection : IP65  
 Keyboard : Micro switches with 2-colour LEDs..  
 Temperature range : Minus 20C° to +70C°. (95% humidity)  
 Dimensions (HxWxD): 313x175x142mm  
 Shipping weight : 3,1Kg



**Model EE8106M**

Digital heavy duty handsfree station 1 call button

Specifications.

Construction : Orange moulded RAL 2004 polyester fiber reinforced.  
 Mounting : wall mounted with 2 screws size M5.  
 Power requirements: 24VAC at 40VA.  
 Cabling : Standard telephone cable 1x2x0,8mm (2Km)  
 Microphone : Standard electret microphone. (Order model EE8107M in order to obtain a station with a noise cancelling microphone.)  
 Audio amplifier : Class "D" at 25Watt at 8 Ohm external speaker.  
 Built in speaker sound pressure: 96dB/1W/1mtr.  
 Frequency range : 200Hz - 7KHz  
 Inputs : 2 inputs.  
 Outputs : 2 outputs 30Vmax/3A.  
 Protection : IP65  
 Buttons : 1 call button. One red led.  
 Temperature range : Minus 20C° to +70C°. (95% humidity)  
 Dimensions (HxWxD): 313x175x142mm  
 Shipping weight : 3,1Kg



**Model EE8238M/PR-14xx**

Digital heavy duty handsfree station full keypad

Specifications.

Construction : Orange moulded RAL 2004 polyester fiber reinforced.  
 Mounting : wall mounted with 2 screws size M5.  
 Power requirements: 24VAC at 40VA.  
 Cabling : Standard telephone cable 1x2x0,8mm (2Km)  
 Microphone : Noise cancelling  
 Audio amplifier : Class "D" at 25Watt at 8 Ohm external speaker.  
 Top speaker sound pressure: 101dB/1W/1mtr.  
 Frequency range : 200Hz - 7KHz  
 Inputs : 2 inputs.  
 Outputs : 2 outputs 30Vmax/3A.  
 Protection : IP65  
 Keyboard : Micro switches with 2-colour LEDs..Full keypad.  
 Temperature range : Minus 20C° to +70C°. (95% humidity)  
 Dimensions (HxWxD): 313x175x142mm  
 Shipping weight : 3,1Kg

The models EE81xxM are digital indoor/outdoor industrial intercom slave stations for heavy duty applications such as chemical plants steel mills paper industry ect...

The communication is open duplex, semi-duplex or simplex, depending of the programming settings. All stations are provided with a red optical indication soon the microphone of the station is activated.

Depending of the model numbers, stations will be provided with a noise cancelling microphone which allows communication into even high noise areas.