IP BASED MASTER STATION MODEL CD800-K32 up to K96.

MODEL CD800-K32/GOS/DIS/HS

Master station with 32 selection buttons, gooseneck microphone, touch screen panel and handset
(Models CD800-K64 and K96 will have additional push button panels)

Features

- Modular Control Desk solution.
- Up to 3 push buttons panels of each 32 direct dial buttons. (Total of 96 buttons)
- IP50 rating.
- Connection for headset, handset or gooseneck microphone available.
- Touch screen panel providing seamless integration of third party software products.

Options



K32
keyboard 32 buttons

GOS
Gooseneck microphone



HS
Handset for privacy

DIS
Touch screen panel

Specifications.

Construction : Poly-carbonate .
Mounting : desk top.
Power requirements: 20-30VDC/10VA.
Cabling : CAT-5 cable. Maximum 90 meter and separate power supply.
Microphone : Electret. External connection for headphone- headset or handset.
Audio amplifier : Class "D" at 2,5Watt . Built in 2 speakers of 8 Ohm.
Inputs/Outputs : 3 input contacts, 2 relay output contacts 30V/1A
Adjustments : volume and ringing tone . Use the up/down arrow.
Frequency range : 200Hz - 16KHz
Display : Small display built in main unit:
- 3,5" TFT display monochrome (CD800P) or colour (CD810P). Resolution 320x240 pixels

Large display touch screen panel:
- 8,4" TFT display colour. Resolution 800x600 pixels. Fanless industrial PC concept.

Keyboard : Up to 96 illuminated LED membrane selection switches. 3 colour LED function.
Technology : latest DSP speech technology for clear communication.
Protection : IP50
Temperature range : 0Cº to +70Cº. (95% humidity)
Dimensions (WxHxD): Ech panel is 262x196x45mm (Gooseneck not included)
Shipping weight : 1,1Kg per panel.

PRONOR **N.V.**
Liefkensstraat 35A
B-9032 GENT

TEL: (+) 32-9-257 08 80
FAX: (+) 32-9-257 08 85

www.pronorbelgium.com
E-mail:info@pronor.be

Pub-0003-162b