

MODEL SL2100/xx VoIP/DIGITAL/ANALOGUE HYBRID PABX UNIT



Model SL2100/xx PABX

(Extension housings not shown)

See "Ordering information" for exact type numbers replacing the "xx".

Specifications.

- Base housing : Empty housing, includes only power supply and 5 empty slots. See lower "Options" requested cards in order to provide the housing with analogue or digital extensions.
- Expansion slots : 4 each per housing. Providing up to max 26 analogue or 32 digital ports and 1 Paging outputs per housing.
- Incoming lines : 3 each by adding card IP7WW-3COIDB-C1. Maximum 36. See lower "Options"
- Music on hold : One (1) music on hold input per housing available. (Meaning max 3)
- Calling numbers : Internal analogue calls starts by dialling "208" up to "267".
Outside lines dial "9" (If trunk line card IP7WW-3COIDB-C1 is installed. See "Options" below)
- Power requirements: 90..264VAC/50-60Hz +/-10% 144-175VA per housing.
- Protection : IP23
- Approvals : CE mark and Europe PTT approvals.
- Max. cable length : 1) Analogue telephones maximum 1,5Km using 0,5mm wire.
2) Digital telephones (XN120 system phones) max. 300mtr.
- Field connection : At PABX side all connections are RJ45 type.
(2 extension per connector)
- Dimensions (WxHxD): 435x93x330mm. (Extension housings will have same dimensions.)
- Operation temp : 0°C to 40°C
- Shipping weight : 2,5Kg (fully equipped). (Extension housings will have same weight each.)

Ordering information. (Noted for analogue subscribers.)

- | | |
|----------------------------------|-------------------------|
| SL2100/02 = PABX 2 subscribers. | } Basic housing |
| SL2100/10 = PABX 10 subscribers. | |
| SL2100/18 = PABX 18 subscribers. | |
| SL2100/26 = PABX 26 subscribers. | |
| SL2100/34 = PABX 34 subscribers. | } 1e extension housing. |
| SL2100/42 = PABX 42 subscribers. | |
| SL2100/50 = PABX 50 subscribers. | |
| SL2100/58 = PABX 58 subscribers. | |
| SL2100/66 = PABX 66 subscribers. | } 2e extension housing. |
| SL2100/74 = PABX 74 subscribers. | |
| SL2100/82 = PABX 82 subscribers. | |
| SL2100/90 = PABX 90 subscribers. | |
| SL2100/96 = PABX 96 subscribers. | |

Options.

- IP7WW-008U-A1 = Extension card 8 analogue lines. (Max. 4 per housing)
- IP7WW-082U-B1 = Extension card 8 digital lines and 2 analogue. (Max. 3 per housing)
- IP7WW-3COIDB-C1 = 3 analogue government (trunk) lines. (Max .4 per housing)
- IP7WW-4KSU-C1 = Expansion housing. (Max. 2 expansion housings.)
- BE116506 = PA audio output card with 8 digital and 2 analogue lines.

The SL2100/xx PABX units are easy to use, easy to install, modular telephone system designed specifically for the needs of the small size business or branch organisation.

The SL2100/xx allows connection of traditional analogue corded or cordless telephones as well as the highly featured digital phones and VoIP telephones.

With simple addition of cards, it can provide capacity for 90 analogue (72 digital) extensions.

CHOICE OF ANALOGUE/DIGITAL TELEPHONES FOR ABOVE PABX



IP4WW-12TXH-B
(Digital office)



TX-250
(Analogue indoor)



256-001
(Analogue outdoor)



ExResist Tel
(Analogue explosion proof)

See individual datasheet for detailed information of above telephones.